

S9600-102XC

Open Aggregation Router

The S9600-102XC open aggregation router, is a multi-function, white box routing platform with an external TCAM. It is equipped with Broadcom's Qumran2c merchant silicon chip and an Intel Skylake processor featuring 96x25G, 6x100G high speed ports with a switching capacity of up to 2.4Tbps.

The S9600-102XC can be deployed at C-RAN hubs to provide 5G fronthaul transport aggregation or be positioned at the backhaul for aggregating BBU pooling. It can also be programmed to be a Broadband Network Gateway (BNG) to enable the next generation broadband network. Equipped with high port density, Class C timing and fully supporting SyncE and IEEE 1588v2, our S9600-102XC is capable of fulfilling the role of any type of network aggregation.

Specializing in 5G Time Sensitive Networking applications, the S9600-102XC complies to the IEEE 802.1CM and can act as an Edge Grandmaster (GM) clock. Our open aggregation router is compatible with high accuracy fronthaul synchronization and timing requirements (ITU-T G.8273.2 T-BC, Class C) to ensure error free operation of 5G and cooperative radio techniques.



KEY BENEFITS

- Enable Time Sensitive Networking for 5G compatibility
- Integrate open NOS applications for highly reliable composable networks
- Futureproof to meet evolving requirements of 5G with ultra-low latency, high precision frequency and phase timing synchronization support
- Quick and easy installation onto standard 19" server racks
- Streamline maintenance with redundant and hot swappable power and fan modules

KEY FEATURES

- High density, 96x25G ports with additional 6x100G ports
- 2.4Tbps switching capacity with an 8-Core, 1.9GHz processor
- 4GB packet buffer
- Hardware supports full SyncE and IEEE 1588v2
- Integrated Stratum 3E OCXO with optional hold over performances
- Class C timing accuracy
- Internal GNSS receiver for master clock implementations
- Rich timing interfaces: GNSS, 10MHz, 1PPS and ToD

SPECIFICATIONS

PHYSICAL

- ◆ 6 x 40/100G QSFP28 ports
- ◆ 96 x 1/10/25G SFP28 ports
- ◆ 2 x 10G SFP+ management ports
- ◆ 1 x RJ45 serial console port
- ◆ 1 x 100/1000M RJ45 management port
- ◆ 1 x USB 3.0 Type-A port

Processor Intel Skylake-D 8-Core @ 1.9GHz

Memory 2 x 16G DDR4 R-DIMM

Storage 1 x 128GB SSD

ASIC Broadcom Qumran2c BCM88820
Broadcom OP2 BCM16K

BMC AST2620

Timing Interfaces 1 x GNSS input SMA
1 x 10MHz input/output SMB
1 x 1PPS input/output SMB
1 x ToD input/output RJ45

Timing Support Stratum 3E OXC0
ITU-T Synchronous Ethernet (SyncE)
IEEE 1588v2 (Default Profile, G.8265.1 G8275.1,
G.8275.2 profiles), T-TC, T-BC/OC, T-GM
Time Sensitive Networking (TSN)

Chassis (WxDxH) 2 RU, 436 x 609 x 87.7 mm
or 17.17" x 23.97" x 3.45"

Redundancy Hot-swappable, 1+1 redundant PSU
Hot-swappable, 3+1 redundant Fans

ENVIRONMENTAL

Power Specs. AC input: 100 to 240V, 12A
DC input: -40 to -75V, 40A
Typical power: 379 Watts (no transceiver)

Max. Operating Specs. Operating temperature: 0°C to 45°C (113°F to 122°F)
Operating humidity: 5% to 85% (RH), non-condensing

Max. Non-Operating Specs. Storage temperature: -40°C to 70°C (-40°F to 122°F)
Storage humidity: 5% to 93% (RH), non-condensing

PERFORMANCE

Switching Capacity 2.4Tbps

Deep Buffer 4GB

REGULATORY COMPLIANCE

Safety UL 62368-1
IEC 62368-1

EMC FCC Part 15, Subpart B, Class A
ICES-003, Class A
EN 55032, Class A
EN 55035
EN 300 386
EN 301 489
EN 303 413


Environment WEEE

Specifications are subject to change without notice.

S9600-102XC

Telecom
Networking
Solutions

S9600-102XC Front and Rear Views



ACCESSORIES

Compatible Transceivers Types

100G QSFP28 SR4, 100G QSFP28 LR4, 100G QSFP28 ER4, 100G QSFP28 ZR4, 25G SFP28 SR, 25G SFP28 LR, 25G SFP28 ER, 10G SFP+ SR, 10G SFP+ LR, 10G SFP+ ER, 1G SFP SX, 1G SFP LX, 1G SFP EX

Compatible Timing Cable Types

50 ohms SMA coaxial cable with 1/4-36UNS-2B connector for GNSS
50 ohms SMB coaxial cable with 10-32UNF-2A connector for 1PPS and 10MHz
Shield cable with RJ45 for ToD

Available to Order

Power Supply Types

PSU-132-DESR, 1300W DC, exhaust air flow
PSU-132-AESR, 1300W AC, exhaust air flow

Fan Types

FAN-803816-HI, exhaust air flow

